


Frese frontali a 2 tagli, serie corta, con standard dimensionali SGS. Elica destra a 30°. Tagli al centro.

BASICARBIDE

Tipologia di lavoro




Ø d ₁ mm	Ø d ₂ mm	l ₁ mm	l ₂ mm	Euro			
				non rivestite	TiN	TiCN	TiALN
1	3	38	4	9,60	10,70	10,70	10,70
1,5	3	38	4,5	9,60	10,70	10,70	10,70
2	3	38	6,3	9,60	10,70	10,70	10,70
2,5	3	38	9,5	9,60	10,70	10,70	10,70
3	3	38	12	8,50	9,60	9,60	9,60
3,5	4	50	12	12,60	14,10	14,10	14,10
4	4	50	14	11,90	13,40	13,40	13,40
4,5	6	50	16	12,70	14,20	14,20	14,20
5	6	50	16	12,70	14,20	14,20	14,20
6	6	50	19	14,50	16,40	16,40	16,40
7	8	63	19	19,50	21,70	21,70	21,70
8	8	63	20	17,80	20,00	20,00	20,00
9	10	75	22	26,60	29,80	29,80	29,80
10	10	75	22	29,80	33,50	33,50	33,50
11	12	75	25	36,60	41,00	41,00	41,00
12	12	75	25	36,60	41,00	41,00	41,00
14	14	89	32	58,80	62,90	62,90	62,90
16	16	89	32	65,80	70,50	70,50	70,50
18	18	100	38	97,10	103,90	103,90	103,90
20	20	100	38	134,90	144,50	144,50	144,50

* A richiesta le frese art. 3M possono essere fornite con attacco Weldon e dimensioni corrispondenti alla tabella DIN 6527. Prezzi a richiesta

Tolleranza

Ø d₁ = +0.000/-0.05 mm
Ø d₂ = +0.000/-0.01 mm


Per dati tecnici e parametri di lavoro vedi pag. 50



Frese frontali a 3 tagli, serie corta, con standard dimensionali SGS. Elica destra a 30°. Tagli al centro.

BASICARBIDE

Tipologia di lavoro



Ø d ₁ mm	Ø d ₂ mm	l ₁ mm	l ₂ mm	Euro			
				non rivestite	TiN	TiCN	TiALN
1	3	38	4	9,60	10,70	10,70	10,70
1,5	3	38	4,5	9,60	10,70	10,70	10,70
2	3	38	6,3	9,60	10,70	10,70	10,70
2,5	3	38	9,5	9,60	10,70	10,70	10,70
3	3	38	12	8,50	9,60	9,60	9,60
3,5	4	50	12	12,60	14,10	14,10	14,10
4	4	50	14	11,90	13,40	13,40	13,40
4,5	6	50	16	12,70	14,20	14,20	14,20
5	6	50	16	12,70	14,20	14,20	14,20
6	6	50	19	14,50	16,40	16,40	16,40
7	8	63	19	19,50	21,70	21,70	21,70
8	8	63	20	17,80	20,00	20,00	20,00
9	10	75	22	26,60	29,80	29,80	29,80
10	10	75	22	29,80	33,50	33,50	33,50
11	12	75	25	36,60	41,00	41,00	41,00
12	12	75	25	36,60	41,00	41,00	41,00
14	14	89	32	58,80	62,90	62,90	62,90
16	16	89	32	65,80	70,50	70,50	70,50
18	18	100	38	97,10	103,90	103,90	103,90
20	20	100	38	134,90	144,50	144,50	144,50
25	25	100	38	173,20	185,40	185,40	185,40

* A richiesta le frese art. 5M possono essere fornite con attacco Weldon e dimensioni corrispondenti alla tabella DIN 6527. Prezzi a richiesta

Tolleranza

Ø d₁ = +0.000/-0.05 mm
Ø d₂ = +0.000/-0.01 mm

Per dati tecnici e parametri di lavoro vedi pag. 50